

Радиомаяки

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727) 345-47-04

Беларусь +(375) 257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: phb@nt-rt.ru || сайт: <https://pepperl-fuchs.nt-rt.ru/>



Bluetooth® Low Energy Beacon

LOC 01 HC

- Compatible with Bluetooth® Low Energy from version 4.0
- Range inside buildings up to 30 m, outdoors up to 200 m (Geolocation)
- Possibility to change important operating parameters "over the air"
- Open firmware for individual BLE profile development (TI CC2541)
- UV-resistant housing according to IP64 (can also be used outdoors)

Loc 01 HC, Rugged/Industrial



Function

The rugged, industrial Bluetooth® Low Energy beacon Loc 01 can be mounted directly to a suitable surface or easily adapted to the optional mounting plate, which facilitates battery replacement of the beacon. The Bluetooth Low Energy standard makes the beacons compatible with today's popular smartphones and tablets. They can be detected by these devices from a distance of up to 200 meters (outdoors). The beacon signals can be interpreted by the mobile device through custom applications, interacting with the user or other programs.

Technical Data

General specifications	
Color	black
Electrical specifications	
Battery type	2x Saft, LS14500 3.6 V, 2600 mAh AA / Mignon / R6 Li-SOCl ₂
Operating duration	approx. 4 years in continuous operation with factory setting
Interface	
Interface type	Bluetooth® Low Energy (from 4.0)
Transmitter frequency	1000 ms
Transmitter radiated power	max. 8 dBm
Detection range	30 m range in buildings, max. 200 m outdoors
Protocol	ECOM Standard compatible with Android™ smartphones
Approvals and certificates	
CE conformity	CE0102
Ambient conditions	
Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
Storage temperature	-30 ... 30 °C (-22 ... 86 °F)
Mechanical specifications	
Mass	approx. 180 g (including batteries)
Dimensions	
W x H x D	111 mm x 102 mm x 48 mm
General information	
Scope of delivery	Loc 01 HC Batteries Documentation



Bluetooth® Low Energy Beacon LOC-EX 01

- Compatible with Bluetooth® Low Energy from version 4.0
- Range inside buildings up to 30 m, outdoors up to 200 m (Geolocation)
- Possibility to change important operating parameters "over the air"
- Open firmware for individual BLE profile development (TI CC2541)
- UV-resistant housing according to IP64 (can also be used outdoors)

Loc-Ex® 01, DIV 1 and Zone 1/21



Function

The intrinsically safe Bluetooth® Low Energy beacon Loc-Ex® 01 can be mounted directly on a suitable surface or easily adapted to the optional mounting plate, which facilitates the replacement of the beacons' batteries. The Bluetooth Low Energy standard makes the beacons compatible with today's popular smartphones and tablets. They can be detected by these devices from a distance of up to 200 meters (outdoors). The beacon signals can be interpreted by the mobile device through custom applications, interacting with the user or other programs.

Technical Data

General specifications

Color	black
-------	-------

Electrical specifications

Battery type	2x Saft, LS14500 3.6 V, 2600 mAh AA / Mignon / R6 Li-SOCl ₂
--------------	---

Operating duration	approx. 4 years (with factory setting)
--------------------	--

Interface

Interface type	Bluetooth® Low Energy (from 4.0)
Transmitter frequency	1000 ms
Transmitter radiated power	max. 8 dBm
Detection range	30 m range in buildings, max. 200 m outdoors
Protocol	ECOM Standard compatible with Android™ smartphones (UUID, Major ID, Minor ID, RX Power)

Approvals and certificates

CE conformity	CE0102
---------------	--------

Ambient conditions

Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
Storage temperature	-30 ... 30 °C (-22 ... 86 °F)

Mechanical specifications

Degree of protection	IP64
Mass	approx. 180 g (including batteries)
Dimensions	
W x H x D	111 mm x 102 mm x 48 mm

Data for application in connection with hazardous areas

ATEX approval	
ATEX certificate	EPS 16 ATEX 1 043 X
ATEX marking	Ⓔ II 2G Ex ia IIC T4 Gb IP64 Ⓔ II 2D Ex ia IIIC T125°C Db IP64

Technical Data

International approvals		
IECEX approval		
IECEX certificate		IECEX EPS 16.0019X
IECEX marking		Ex ia IIC T4 Gb IP64 Ex ia IIIC T125°C Db IP64
NEC/CEC approval		
NEC/CEC certificate		70105641
NEC/CEC marking		Class I, II, III, Division 1 Groups A-G, T4 Class I, Zone 1, AEx ia IIC T4 Gb Ex ia IIC T4 Gb Class II, Zone 21, AEx ia IIIC T125°C Db IP64 Ex ia IIIC T125°C Db IP64
General information		
Scope of delivery		Loc-Ex® 01 Batteries Documentation



Bluetooth® Low Energy Beacon

LOC 01 SC

- Compatible with Bluetooth® Low Energy from version 4.0
- Range inside buildings up to 30 m, outdoors up to 200 m (Geolocation)
- Possibility to change important operating parameters "over the air"
- Open firmware for individual BLE profile development (TI CC2541)
- UV-resistant housing according to IP64 (can also be used outdoors)

Loc 01 SC, Rugged/Industrial



Function

The rugged, industrial Bluetooth® Low Energy beacon Loc 01 can be mounted directly to a suitable surface or easily adapted to the optional mounting plate, which facilitates battery replacement of the beacon. The Bluetooth Low Energy standard makes the beacons compatible with today's popular smartphones and tablets. They can be detected by these devices from a distance of up to 200 meters (outdoors). The beacon signals can be interpreted by the mobile device through custom applications, interacting with the user or other programs.

Technical Data

General specifications	
Color	black
Electrical specifications	
Battery type	Panasonic Powerline, LR06 1.5 V AA / Mignon / R6 Alkaline
Operating duration	approx. 2 years in continuous operation with factory setting
Interface	
Interface type	Bluetooth® Low Energy (from 4.0)
Transmitter frequency	1000 ms
Transmitter radiated power	max. 8 dBm
Detection range	30 m range in buildings, max. 200 m outdoors
Protocol	ECOM Standard compatible with Android™ smartphones (UUID, Major ID, Minor ID, RX Power)
Software	
Approvals and certificates	
CE conformity	CE0102
Ambient conditions	
Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
Storage temperature	-30 ... 30 °C (-22 ... 86 °F)
Mechanical specifications	
Degree of protection	IP64
Mass	approx. 180 g (including batteries)
Dimensions	
W x H x D	111 mm x 102 mm x 48 mm
General information	
Scope of delivery	Loc 01 SC Batteries Documentation



Bluetooth® Low Energy Beacon LOC-EX 01 FULLY IBEACON PROT.

- Compatible with Bluetooth® Low Energy from version 4.0
- Range inside buildings up to 30 m, outdoors up to 200 m (Geolocation)
- Possibility to change important operating parameters "over the air"
- Open firmware for individual BLE profile development (TI CC2541)
- UV-resistant housing according to IP64 (can also be used outdoors)

Loc-Ex® 01, DIV 1 and Zone 1/21



Bluetooth®



Function

The intrinsically safe Bluetooth® Low Energy beacon Loc-Ex® 01 can be mounted directly on a suitable surface or easily adapted to the optional mounting plate, which facilitates the replacement of the beacons' batteries.

The Bluetooth Low Energy standard makes the beacons compatible with today's popular smartphones and tablets. They can be detected by these devices from a distance of up to 200 meters (outdoors). The beacon signals can be interpreted by the mobile device through custom applications, interacting with the user or other programs.

iBeacon sensors create a small, concentrated area of detection. Within the transmission zone, customized notifications can be sent to iBeacon-enabled apps on iPhone, iPad, or Apple Watch devices that support current Bluetooth technology. Customers can be alerted to everything from special offers and discounts to personalized messages and details about a display.

Technical Data

General specifications

Color	black
-------	-------

Electrical specifications

Battery type	2x Saft, LS14500 3.6 V, 2600 mAh AA / Mignon / R6 Li-SOCl ₂
--------------	---

Operating duration	approx. 4 years (with factory setting)
--------------------	--

Interface

Interface type	Bluetooth® Low Energy (from 4.0)
Transmitter frequency	1000 ms
Transmitter radiated power	max. 8 dBm
Detection range	30 m range in buildings, max. 200 m outdoors
Protocol	iBeacon (UUID, Major ID, Minor ID, RX Power)

Approvals and certificates

CE conformity	CE0102
---------------	--------

Ambient conditions

Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
Storage temperature	-30 ... 30 °C (-22 ... 86 °F)

Mechanical specifications

Degree of protection	IP64
Mass	approx. 180 g (including batteries)
Dimensions	
W x H x D	111 mm x 102 mm x 48 mm

Data for application in connection with hazardous areas

ATEX approval	
ATEX certificate	EPS 16 ATEX 1 043 X

Technical Data

ATEX marking		Ⓔ II 2G Ex ia IIC T4 Gb IP64 Ⓔ II 2D Ex ia IIIC T125°C Db IP64
International approvals		
IECEX approval		
IECEX certificate		IECEX EPS 16.0019X
IECEX marking		Ex ia IIC T4 Gb IP64 Ex ia IIIC T125°C Db IP64
NEC/CEC approval		
NEC/CEC certificate		70105641
NEC/CEC marking		Class I, II, III, Division 1 Groups A-G, T4 Class I, Zone 1, AEx ia IIC T4 Gb Ex ia IIC T4 Gb Class II, Zone 21, AEx ia IIIC T125°C Db IP64 Ex ia IIIC T125°C Db IP64
General information		
Note		Use of the Works with Apple iBeacon badge means that a product has been designed and certified by the manufacturer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this product with iPod, iPhone, or iPad may affect wireless performance.
Scope of delivery		Loc-Ex® 01 Batteries Documentation

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727) 345-47-04

Беларусь +(375) 257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: phb@nt-rt.ru || сайт: <https://pepperl-fuchs.nt-rt.ru/>